

# SMT Shielded Power Inductors


## GS5022DC

### Features (特長)

- Magnetically shielded construction (閉磁路構造設計)
- Compact and thin (輕便薄小)
- Large Current and Low DCR (大電流及低直流阻抗)

### Applications (用途)

- Notebook, DC/DC converter, VGA card, Video recorders. (筆記型電腦、直流轉換器、電腦顯示卡、錄影機)




### Product Identification (產品識別)

GS5022DC - \_\_\_\_\_ (Ex. GS5022DC-100M)

1                      2                      3

1. SMT Shielded Power Inductors (閉磁式功率電感) (GS5022DC)
2. Inductance (電感值)
3. Tolerance (誤差值) ( 參照表 M 20%, N 30% )

### Configurations & Dimensions (結構圖及規格尺寸)



Unit In mm

Type (型式)	A (max)	B (max)	C ±0.3	D (max)	E ±0.3	F ±0.3	G ±0.3	I	J	K
GS5022DC	18.54	15.24	12.70	7.62	2.54	2.54	12.70	2.79	3.30	12.45

♣ Design as Customer's Requested Specifications. (可依客戶特殊需求設計)

# SMT Shielded Power Inductors

## GS5022DC

Electrical Characteristics for GS5022DC Series [GS5022DC 系列電子特性規格]

Part Number 產品料號	Inductance ( $\mu$ H) 電感值 (L)	Test Freq. (KHz) 測試頻率	DCR ( $\Omega$ ) (max) 直流阻抗	IDC (A) (max) 定格電流
GS5022DC – 100M	10.00	100	0.040	8.00
GS5022DC – 150M	15.00	100	0.048	7.00
GS5022DC – 220M	22.00	100	0.059	6.00
GS5022DC – 330M	33.00	100	0.075	5.00
GS5022DC – 470M	47.00	100	0.097	4.00
GS5022DC – 680M	68.00	100	0.138	3.00
GS5022DC – 101M	100.00	100	0.207	2.40
GS5022DC – 151M	150.00	100	0.293	2.10
GS5022DC – 221M	220.00	100	0.470	1.90
GS5022DC – 331M	330.00	100	0.780	1.10
GS5022DC – 471M	470.00	100	1.080	1.10
GS5022DC – 681M	680.00	100	1.400	0.96
GS5022DC – 102M	1000.00	100	2.010	0.80

※Test Freq. : 100KHz / 0.1V.

※Operating Temp. :  $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$

※Inductance drop = 10% typ. at IDC.

※Storage Temperature&Humidity :  $\leq 40^{\circ}\text{C}$  & 70% RH maximum